



tesa® 4651

Product Information

Premium Acrylic Coated Colored Cloth Tape

Product Features

- The cloth tape is conformable and features excellent abrasion resistance, high tensile strength, as well as a very high adhesiveness to multiple, even rough surfaces.
- The tape's high tack and short dwell time ensure a fast application and reliable adhesion only shortly after having been applied.
- The tape can be torn manually with precise and straight edges longitudinally and horizontally.
- Classification according FMVSS302: SE/NBR*

Product Description

tesa® 4651 is a robust, high-quality, acrylic coated cloth tape. It is based on a 145 mesh woven rayon fabric backing and a natural rubber adhesive. The product is also available with paper liner in jumbo-roll format (tesa® 4651 PV9).

Application Fields

- Masking while sandblasting, coating, paint spraying, etc
- Bundling and reinforcing of freight, such as pipes or profiles
- Labeling, color coding or marking of wires, cables, etc
- Permanent sealing of pipe joints, tins and tubes

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Thickness of tape	310 µm	• Backing material	Acrylic-coated cloth
• Color of liner	yellow	• Type of adhesive	natural rubber
• Total thickness	310 µm	• Type of liner	paper
• Thickness of liner	76 µm		

Properties/Performance Values

• Elongation at break	13 %	• Hand tearability	very good
• Temperature resistance	130 °C	• Mesh	145 count per square inch
(removability from aluminum after 30 min exposure)		• Abrasion resistance	very good
• Straight tear edges	very good	• Water resistance	good
• Tensile strength	100 N/cm		
• Easy to write on	Yes		

For latest information on this product please visit
<http://l.tesa.com/?ip=04651>



tesa® 4651

Product Information

Adhesion to Values

- steel 3.3 N/cm

Additional Information

*self-extinguishing / no burn rate according FMVSS 302 tested as composite with a non-flammable material

Complies with LV 312-1 Dielectric strength

The following RAL-Codes reflect our product coloring:

- RAL 9005 Black - tesa color code: 04
- RAL 9010 White - tesa color code: 08
- RAL 7000 Gray - tesa color code: 55
- RAL 1016 Yellow - tesa color code: 17
- RAL 3000 Red - tesa color code: 19
- RAL 5015 Blue - tesa color code: 11
- RAL 6018 Green - tesa color code: 37
- RAL 8003 Brown - tesa color code: 45

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=04651>